

## C2-Frame

### Description



**Code: C2**

It's a bar bearing support equipped with a roller. It can be used in addition to the roller table. It should be suitably ballasted or fixed to the floor. Roller 550 mm wide - max load 750 kg. H min 840 mm / H max 1.015 mm

## CRC-Loading side connection

### Description



**Code: CRC**

CRC - Roller table-machine connection on loading side.

## CRS-Connection in unloading side

### Description



**Code: CRS**

It's the unloading side connection between machine and roller table.

## FM..RI-LENGTH STOP WITH HYDRAULIC ARTICULATED STRIKER

### Description



**Code:** *FM..RI*

Length stop on unloading side with hydraulic cylinder for the backing of the stroke reference during the cut. Available lengths from 1 m to 6 m.

#### **FM..RS-Length stop with articulated striker**

##### **Description**



**Code:** *FM..RS*

The material must always be cut according to a prearranged length. The machine may be equipped with a length stop for 1 to 6 meters [3.3 to 19.7 ft] measure stops to be installed on the RP roller tables.

#### **RM-Motorized roller**

##### **Description**



**Code:** *RM-Rullo motorizzato*

The RM motorized roller is generally placed near the band saw on the loading side; in this way the roller support surface is placed under the piece to be moved. Switching on the feeding selector, the roller automatically raises a few millimeters lifting the bar to be cut. Once the maximum quota is reached, the roller begins to turn moving the piece towards the selected direction: the selector turned anticlockwise makes the bar move backward, while turned clockwise makes it move forward. Releasing the selector, the roller automatically stops and goes down: so for its use the presence of an operator is always necessary. The roller rotation speed can be adjusted before or even during its moving (for instance going fast at the beginning and then slower during blade approach). Our motorized roller can be joined to all models of FMB band saws so that any movement is avoided during the cut. Its moving is electrical and its lifting power is 1,500 kg.

## RP1G-RP2G Roller tables

### Description



**Code:** *RP1G - RP2G*

To work safely, the material to be cut should lean on roller tables as long as necessary on both loading and unloading sides. FMB s.r.l. can supply this optional:

- Roller table RP2G (1° module ) - Two legs 1 m long roller table with 400mm wide idle rollers and max. load 300 kg/m.
- Roller table RP1G (Following) - One leg 1 m long roller table with 400mm wide idle rollers and max. load 300 kg/m.

## RRS-Unloading side pull-out roller surface

### Description



**Code:** *RRS*

It's the unloading side connection between machine and roller table.