

C2-Frame

Description



Code: C2

It's a bar bearing support equipped with a roller. It can be used in addition to the roller table. It should be suitably ballasted or fixed to the floor. Roller 550 mm wide - max load 750 kg. H min 840 mm / H max 1.015 mm

CNP-Digital measuring reading system with automatic striker positioning

Description



Code: CNP

CNP- Unloading side roller table to measure the material. System equipped with a measuring striker with automatic positioning controlled by a programmable electronic panel. Feeding is made by a pinion on rack through a gear box controlled by an inverter.

Tilting striker arm equipped with a locking brake with springs shocks absorber. 550mm wide idle rollers, diameter 70 mm and max loading capacity of 1000 Kg/m.

H min 925 mm/H max 980 mm.

FM..RSP-Heavy length stops

Description



Code: FM..RSP

The material must always be cut according to a prearranged length. The machine may be equipped with a measure shaft for 1 to 6 meters [3.3 to 19.7 ft] measure

stops to be installed on the RP roller tables.

RFP2-roller table

Description



Code: *RFP2*

2 m long roller table with idle rollers 550mm wide, max load 1000Kg/m. (h min 935 mm / h max 1015 mm)

RM-Motorized roller

Description



Code: *RM-Rullo motorizzato*

The RM motorized roller is generally placed near the band saw on the loading side; in this way the roller support surface is placed under the piece to be moved. Switching on the feeding selector, the roller automatically raises a few millimeters lifting the bar to be cut. Once the maximum quota is reached, the roller begins to turn moving the piece towards the selected direction: the selector turned anticlockwise makes the bar move backward, while turned clockwise makes it move forward. Releasing the selector, the roller automatically stops and goes down: so for its use the presence of an operator is always necessary. The roller rotation speed can be adjusted before or even during its moving (for instance going fast at the beginning and then slower during blade approach). Our motorized roller can be joined to all models of FMB band saws so that any movement is avoided during the cut. Its moving is electrical and its lifting power is 1,500 kg.