

DOTM-Vertical vice

Description



Code: *DOTM*

Device for vertical clamping of the material, hydraulic cylinder and manual positioning. During the cutting cycle the vertical cylinder works together with the vice for the material clamping.

LX-Laser lighting for cutting line

Description



Code: *LX*

The option LX facilitates the operator during the cutting phase: a luminous red line (laser light) is projected on the piece locked in the vice to exactly display where the blade will make the cut.

NB1-One nozzle sprayer

Description



Code: *NB1*

The band saw machine can be equipped of a blade and cutting cooling device. To improve the cutting quality and reduce pollution risk, moreover to avoid the risk of pools of cooling liquid on the floor (possible cause of accidental falls), the use of the NB optional is particularly suggested.

RMP1

Description



Code: *RPM1*

The closing pressure adjustment of the vice RPM1, decreasing from the standard machine max. pressure, is used for materials having thin thickness and consequently that can be easily deformed. It is not possible to reduce the pressure value adjusted by the hydraulic system pressure switch under the safety value of 6 bar.

SENS-Control blade rotation

Description



Code: *SENS*

The SENS optional is assembled on the flywheel. In case the blade collapses due to an insufficient tension exerted by the stretcher or in case it goes stuck into the piece during the cut, the work cycle would immediately stop. In this way the SENS optional protects the motor wheel and the blade itself.

TM - H34

Description



Code: *TM - H34*

This option allows a considerable reduction in working times: it speeds up the descent of the blade and decreases its lifting speed. On the head there is a fast approach device allowing the rapid approach of the blade when this is near the work piece to be cut. After cutting, the blade goes back only what is strictly necessary out of the piece and it is immediately ready for the next cut.