

LX-Laser lighting for cutting line

Description



Code: *LX*

The option LX facilitates the operator during the cutting phase: a luminous red line (laser light) is projected on the piece locked in the vice to exactly display where the blade will make the cut.

NB1-One nozzle sprayer

Description



Code: *NB1*

The band saw machine can be equipped of a blade and cutting cooling device. To improve the cutting quality and reduce pollution risk, moreover to avoid the risk of pools of cooling liquid on the floor (possible cause of accidental falls), the use of the NB optional is particularly suggested.

RMP1

Description



Code: *RMP1*

The closing pressure adjustment of the vice RMP1, decreasing from the standard machine max. pressure, is used for materials having thin thickness and consequently that can be easily deformed. It is not possible to reduce the pressure value adjusted by the hydraulic system pressure switch under the safety value of 6 bar.

Description



Code: *RPM2*

This optional allows you to adjust the pressure of the clamping of the cutter vice and the carriage vice. Adjustment must be made separately for each vice and is done by hand, using the handwheel of the valve. The pressure gauge lets you read the pressure change (in bar).

TI-Hydraulic stretcher

Description



Code: *TI*

The option Ti allows carrying out the blade tensioning always correctly and when the machine is off, it allows the blade to loosen avoiding a useless static work. A micro switch controls that the blade is tensioned and, in case of the blade breaking, it stops all the other machine movements.