

SOLAR

SEGATRICE A NASTRO SEMIAUTOMATICA VERTICALE PER TAGLI DA 0° A 60° A SINISTRA E DA 0° A 60° A DESTRA
SEMI-AUTOMATIC VERTICAL BAND SAW MACHINE FOR CUTS FROM 0° TO 60° LEFT AND FROM 0° TO 60° RIGHT



	Ø	a b axb	a b axb
0°	460 mm	460 mm	560x460 mm
45°→	356 mm	356 mm	356x460 mm
60°→	205 mm	205 mm	205x460 mm
←45°	385 mm	385 mm	385x460 mm
←60°	254 mm	254 mm	254x460 mm

20 **35** YEARS EXPERIENCE **PLUS**



Standard

- Rotazione lama tramite inverter
- Fermi di battuta a -60° e +60°
- Pannello comandi touch screen con contapezzi e visualizzazione velocità avanzamento arco
- Lama inclinata di 4,5° rispetto al piano
- Posizionamento automatico dell'arco a gradi tramite pannello touch screen
- SD - Stress detector
- SENS - Sensore rotazione lama



- Blade rotation by inverter
- Stops at -60° and +60°
- Touch screen control panel with piece-counter and head approach speed visualisation
- Blade inclined 4,5° to the surface
- Automatic head degrees positioning by touch screen control panel
- SD - Stress detector
- SENS - Blade rotation sensor

Optional

DMS - LX - NB1 BOX - RPM1 - DMS+RPM2 - TI - RTR/S

Dotazioni accessorie Accessory equipments

C2 - RFP2S - FM...RSP



Faretto per illuminazione piano di taglio.
Lamp lighting the cutting zone.



Movimentazione carro su guide lineari.
Carriage moving on linear guides.



Pannello comandi touch screen con contapezzi e visualizzazione velocità avanzamento arco.
Touch screen control panel with piece-counter and head approach speed visualisation.



SOLAR+DMS



FMB si riserva il diritto di modificare i dati indicati senza necessità di preavviso.
FMB srl reserves the right to modify any data quoted above without previous notice.